
## Elite Stepped Plate Range - Antique Brass

TV/Satellite Socket - S91.926.BK



Range Product Insert Type Plate Finish Switch Colour Body and Switch Trim Height Width Fixing Hole Centres Minimum Box Depth Voltage Power Terminal Capacity Froduct Class 1 Ambient Operating Temperature Recommended Location Standard Vise Tiv/Satellite Socket Antique Brass Antique B			
Insert Type Plate Finish Switch Colour Body and Switch Trim Black Height Width Fixing Hole Centres Minimum Box Depth Voltage 230 V Power Terminal Capacity Farth Terminal Capacity Product Class 1 Ambient Operating Temperature Recommended Location  Pixing Hole Socket Antique Brass Antique Brass  TV/Satellite Socket Antique Brass  TV/Satellite Socket  Antique Brass  TV/Satellite Socket  Antique Brass  Flack Back Back Back Back Back Back Back B	Range	Elite Stepped Plate Range	
Plate Finish Switch Colour - Body and Switch Trim Black Height 86 mm Width 86 mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 35 Current - Voltage 230 V Power - Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Indoor use only	Product	Stepped Plate Antique Brass S91	
Switch Colour Body and Switch Trim Black Height 86 mm  Kining Hole Centres Box Fixing = 60.3 mm  Minimum Box Depth 35  Current - Voltage 230 V  Power - Terminal Capacity 4 mm2  Earth Terminal Capacity 5 mm2  Product Class 1 Face plate must be earthed  Ambient Operating Temperature -5°C - 40°C  Recommended Location Indoor use only	Insert Type	Insert Type TV/Satellite Socket	
Body and Switch Trim Height 86 mm Width 86 mm  Fixing Hole Centres Box Fixing = 60.3 mm  Minimum Box Depth Current Voltage 230 V  Power Terminal Capacity Farth Terminal Capacity Product Class 1 Face plate must be earthed Ambient Operating Temperature Recommended Location Indoor use only	Plate Finish	Antique Brass	
Height Width 86 mm  Fixing Hole Centres Box Fixing = 60.3 mm  Minimum Box Depth 35  Current - Voltage 230 V  Power - Terminal Capacity 4 mm2  Earth Terminal Capacity 5 mm2  Product Class 1 Face plate must be earthed  Ambient Operating Temperature -5°C - 40°C  Indoor use only	Switch Colour	-	
Width Fixing Hole Centres Box Fixing = 60.3 mm  Minimum Box Depth Current Voltage 230 V  Power Terminal Capacity Earth Terminal Capacity Product Class 1 Face plate must be earthed Ambient Operating Temperature Recommended Location Indoor use only	Body and Switch Trim	Black	
Fixing Hole Centres Minimum Box Depth  Current Voltage Power Terminal Capacity Earth Terminal Capacity Product Class 1 Face plate must be earthed Ambient Operating Temperature Recommended Location Recommended Location  Box Fixing = 60.3 mm 35 4 mm 2	Height	86 mm	
Minimum Box Depth Current Voltage 230 V  Power Terminal Capacity Earth Terminal Capacity Product Class 1 Face plate must be earthed Ambient Operating Temperature Recommended Location Indoor use only	Width	86 mm	
Current Voltage 230 V  Power - Terminal Capacity Earth Terminal Capacity Product Class 1 Face plate must be earthed Ambient Operating Temperature Recommended Location Indoor use only	Fixing Hole Centres	Box Fixing = 60.3 mm	
Voltage Power Terminal Capacity Earth Terminal Capacity Product Class 1 Face plate must be earthed Ambient Operating Temperature Recommended Location  Voltage 230 V 4 mm2 5 mm2 Face plate must be earthed -5°C - 40°C Indoor use only	Minimum Box Depth	35	
Power Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Current	-	
Terminal Capacity 4 mm2  Earth Terminal Capacity 5 mm2  Product Class 1 Face plate must be earthed  Ambient Operating Temperature -5°C - 40°C  Recommended Location Indoor use only	Voltage 230 V		
Earth Terminal Capacity 5 mm2  Product Class 1 Face plate must be earthed  Ambient Operating Temperature -5°C - 40°C  Recommended Location Indoor use only	Power -		
Product Class 1 Face plate must be earthed  Ambient Operating Temperature -5°C - 40°C  Recommended Location Indoor use only	Terminal Capacity	erminal Capacity 4 mm2	
Ambient Operating Temperature -5°C - 40°C  Recommended Location Indoor use only	Earth Terminal Capacity	5 mm2	
Recommended Location Indoor use only	Product Class 1	Face plate must be earthed	
·	Ambient Operating Temperature	-5°C - 40°C	
Standard BS 3041	Recommended Location	Indoor use only	
Standard DS 3041	Standard	BS 3041	

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN 9001:2008 Quality System.	It is the policy of the company to continually improve products as part of our development program.  Therefore, we respect the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are produced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing process we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as 01.01.2016. E&OE

## **British Standards**

The Heritage Brass Electrical Collection is designed and manufactured to comply with the requirements of the relevant British Standards. M Marcus Ltd.

Telephone: +44 (0)1384 247 845 Fax 01384 243 312

Email: electsales@m-marcus.com Website: www.m-marcus.com