
Elite Flat Plate Range - Satin Brass

2 Gang TV Coaxial Socket - T04.922.W



Range Elite Flat Plate Range Product Elite Flat Plate Satin Brass T04 Insert Type 2 Gang TV Coaxial Socket Plate Finish Satin Brass Switch Colour - Body and Switch Trim White Height 86 mm Width 86 mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 35 Current - Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only Standard BS 3041			
Insert Type Plate Finish Switch Colour Body and Switch Trim White Height 86 mm Width Fixing Hole Centres Minimum Box Depth Voltage 230 V Power Terminal Capacity Farth Terminal Capacity Product Class 1 Face plate must be earthed Ambient Operating Temperature Satin Brass Ambient Socket Facin Brass Satin Brass Satin Brass Ambient Socket Facin Brass Satin Brass Facin	Range	Elite Flat Plate Range	
Plate Finish Satin Brass Switch Colour - Body and Switch Trim White Height 86 mm Width 86 mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 35 Current - Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Product	Elite Flat Plate Satin Brass T04	
Switch Colour Body and Switch Trim White Height 86 mm Width 86 mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 35 Current - Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Insert Type	2 Gang TV Coaxial Socket	
Body and Switch Trim White Height 86 mm Width 86 mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 35 Current - Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Plate Finish	Plate Finish Satin Brass	
Height 86 mm Width 86 mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 35 Current - Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Switch Colour	-	
Width 86 mm Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 35 Current - Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Body and Switch Trim	White	
Fixing Hole Centres Box Fixing = 60.3 mm Minimum Box Depth 35 Current - Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Height	86 mm	
Minimum Box Depth Current Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Width	86 mm	
Current - Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Fixing Hole Centres	Box Fixing = 60.3 mm	
Voltage 230 V Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Minimum Box Depth	35	
Power - Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Current	-	
Terminal Capacity 4 mm2 Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Voltage	230 V	
Earth Terminal Capacity 5 mm2 Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Power	-	
Product Class 1 Face plate must be earthed Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Terminal Capacity	4 mm2	
Ambient Operating Temperature -5°C - 40°C Recommended Location Indoor use only	Earth Terminal Capacity	5 mm2	
Recommended Location Indoor use only	Product Class 1	Face plate must be earthed	
·	Ambient Operating Temperature	-5°C - 40°C	
Standard BS 3041	Recommended Location	Indoor use only	
	Standard	BS 3041	

,	All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN 9001:2008 Quality System.	It is the policy of the company to continually improve products as part of our development program. Therefore, we respect the right to alter designs and dimensions without prior notice.
	Illustrations and diagrams are produced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing process we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as 01.01.2016. E&OE

British Standards

The Heritage Brass Electrical Collection is designed and manufactured to comply with the requirements of the relevant British Standards. M Marcus Ltd.

Telephone: +44 (0)1384 247 845 Fax 01384 243 312

Email: electsales@m-marcus.com Website: www.m-marcus.com